

## SMART CAMERA

Series	Image	Model	Specifications
<b>H.265</b> <b>3M@30fps</b> <b>2M@60fps</b>		TC-NC9101S3E-3MP-EI-IR30(2.8-12mm)	<b>PoE</b> , 3MP(2048x1536)@25/30fps; 2MP@60fps, Smart IVA functions; WDR, NIR, BLC, Dual ICR, 30m IR, IP67 Metal Housing, <b>Motorized Lens</b> 2.8-12mm Optional Model:TC-NC9101S3E-3MP-EI-IRW30(2.8-12mm),IR+White Light
		TC-NC9201S3E-3MP-EI-IR30(2.8-12mm)	<b>PoE</b> , 3MP(2048x1536)@25/30fps; 2MP@60fps, Smart IVA functions; WDR, NIR, BLC, Dual ICR, 30m IR, IP67, Vandalproof IK10 Metal Housing, <b>Motorized Lens</b> 2.8-12mm, <b>Internal interfaces</b>
		TC-NC9001S3E-3MP-EI	<b>PoE</b> , 3MP(2048x1536)@25/30fps; 2MP@60fps, <b>Smart IVA functions</b> ; WDR, NIR, BLC, Dual ICR
<b>H.265</b> <b>4M@25fps</b>		TC-NC9101S3E-4MP-E-I5(2.8-12mm) <b>Motorized Lens</b>	PoE, 4MP(2560x1440)@25fps; WDR, NIR, BLC, Dual ICR, 2.8-12mm Motorized Lens 30-50m IR, IP66, 4mm Lens optional, Alarm I/O, Audio I/O, Smart IVA function
		TC-NC9201S3E-4MP-E-I3(2.8-12mm) <b>Motorized Lens</b>	PoE, 4MP(2560x1440)@25fps; WDR, NIR, BLC, Dual ICR, 2.8-12mm Motorized Lens 30m IR, IP66, Vandal-proof, 4mm Lens optional, Alarm I/O, Audio I/O, Smart IVA function
		TC-NC9401S3E-4MP-E-I(6mm)	PoE, 4MP(2560x1440)@25fps; WDR, NIR, BLC, Dual ICR, 6mm Lens 20m IR, IP66, Metal Housing, 4mm Lens optional, <b>Smart IVA function</b>
		TC-NC9501S3E-4MP-E-I(2.8mm)	PoE, 4MP(2560x1440)@25fps; WDR, NIR, BLC, Dual ICR, 2.8mm Lens 20m IR, IP66, 4mm Lens optional, <b>Smart IVA function</b>
		TC-NC9501S3E-4MP-E-I2(2.8mm)	PoE, 4MP(2560x1440)@25fps; WDR, NIR, BLC, Dual ICR, 2.8mm Lens 20m IR, IP66, Vandal-proof, 4mm Lens optional, <b>Smart IVA function</b>
		TC-NC9101S3E-4MP-E-I5(6mm)	PoE, 4MP(2560x1440)@25fps; WDR, NIR, BLC, Dual ICR, 2.8mm Lens 30-50m IR, IP66, 4mm Lens optional, Alarm I/O, Audio I/O, <b>Smart IVA function</b>
		TC-NC9201S3E-4MP-E-I3(2.8mm)	PoE, 4MP(2560x1440)@25fps; WDR, NIR, BLC, Dual ICR, 2.8mm Lens 30m IR, IP66, Vandal-proof, 4mm Lens optional, Alarm I/O, Audio I/O, <b>Smart IVA function</b>
<b>1080P</b> <b>Fixed Lens</b> <b>Mini</b>		TC-NC9400S3E-2MP-E-IR20(6mm)	<b>PoE</b> , 1080P@25/30fps, WDR, NIR, BLC, Dual ICR, 6mm Lens 20m IR, IP66, Metal Housing, 4mm Lens optional
		TC-NC9500S3E-2MP-E-IR20(2.8mm)	<b>PoE</b> , 1080P@25/30fps, WDR, NIR, BLC, Dual ICR, 2.8mm Lens 20m IR, IP66, Metal + Plastic Housing, 4mm Lens optional
		TC-NC9200S3E-2MP-E-IR25(2.8mm)	<b>PoE</b> , 1080P@25/30fps, WDR, NIR, BLC, Dual ICR, 2.8mm Lens 25m IR, IP66, Metal Housing, Vandalproof IK10, 4mm Lens optional
		TC-NC9500S3E-2MP-E-IR30(2.8mm)	<b>PoE</b> , 1080P@25/30fps, WDR, NIR, BLC, Dual ICR, 6mm Lens 30m IR, IP66, Metal Housing, 4mm Lens optional
<b>1080P</b> <b>Varifocal</b> <b>Lit-S</b>		TC-NC9100S3E-2MP-E-I3C(2.8-12mm)	<b>PoE</b> , 1080P@25/30fps, WDR, BLC, Dual ICR, 2.8-12mm lens, 30-50m IR, Audio I/O, Alarm input; IP66, Metal Housing <i>Fix Iris, Plastic lens tube, -20 ℃~60 ℃</i>
		TC-NC9200S3E-2MP-E-I5C(2.8-12mm)	<b>PoE</b> , 1080P@25/30fps, WDR, BLC, Dual ICR, 2.8-12mm lens 30-50m IR, Audio I/O, Alarm input; Vandalproof IK10 <i>Fix Iris, Plastic lens tube, -20 ℃~60 ℃, IP66, Metal Housing</i>
<b>1080P</b> <b>Project</b>		TC-NC9000S3E-2MP-E	<b>PoE</b> , 1080P@25/30fps, Micro SD, WDR, NIR, BLC, Dual ICR Audio I/O, Alarm input, without lens and bracket
		TC-NC9320S3E-2MP-E 20x Zoom	<b>PoE</b> , 1080P@25/30fps, WDR, USB, Audio I/O, Alarm I/O, BNC, RS485 20x Optical Zoom(f=4.7-94mm), Auto-focus, TVS 4000V Lightning-proof
		TC-NC9100S3E-2MP-IR80(4.7-94mm) 80m IR	Super 80m IR, 1080P@25/30fps, 20x Optical Zoom(f=4.7-94mm) WDR, USB, Audio I/O, Alarm I/O, BNC, RS485 Auto-focus, TVS 4000V Lightning-proof, Wiper,
<b>960P</b> <b>Fixed Lens</b> <b>Mini</b>		TC-NC9400S3E-MP-E-IR20(6mm)	<b>PoE</b> , 960P@25/30fps, WDR, NIR, BLC, Dual ICR, 4/6mm Lens 20m IR, IP66, Metal Housing
		TC-NC9500S3E-MP-E-IR20(2.8mm)	<b>PoE</b> , 960P@25/30fps, WDR, NIR, BLC, Dual ICR, 2.8/4mm Lens 20m IR, IP66, Metal Housing
Bracket		TC-713/714S3E	713:Wall bracket for vandalproof dome camera TC-NC9200S3E-2MP-E-IR30 714:Wall bracket for vandalproof dome camera TC-NC9200S3E-2MP-E-IR25

## SMART CAMERA

Series	Image	Model	Specifications
<b>DarkFighte Starlight Box</b>		TC-NC9000S3E-2MP-ES	<b>PoE</b> , 1080P@25/30fps, 1/1.9" 2.0MP Exmor CMOS Low illumination 0.002LUX(Color), WDR 120dB, TVS 4000V Lightning-proof Audio I/O, Alarm input, without lens and bracket
<b>Starlight 1080P</b>		TC-NC9100S3E-2MP-E-I5S(2.8-12mm) <b>Motorized Lens</b>	PoE, H.264 High Profile, 0.002lux 1080P@25/30fps, WDR, NIR, BLC, Dual ICR, 2.8-12mm Motorized Lens 30-50m IR with 4 Array LEDs, IP66, Audio In/Out, Alarm In, USB
		TC-NC9200S3E-2MP-E-I3S(2.8-12mm) <b>Motorized Lens</b>	PoE, H.264 High Profile, 0.002lux 1080P@25/30fps, WDR, NIR, BLC, Dual ICR, 2.8-12mm Motorized Lens 30m IR, IP66, Metal Housing, Audio In/Out, Alarm In, USB
		TC-NC9400S3E-2MP-E-IS	PoE, H.264 High Profile, 0.002lux 1080P@25/30fps, WDR, NIR, BLC, Dual ICR, 4/6mm Lens 20m IR, IP66, Metal Housing
		TC-NC9500S3E-2MP-E-IS	PoE, H.264 High Profile, 0.002lux 1080P@25/30fps, WDR, NIR, BLC, Dual ICR, 2.8/4mm Lens 20m IR, IP66, Metal Housing
		TC-NC9500S3E-2MP-E-I2S	PoE, H.264 High Profile, 0.002lux 1080P@25/30fps, WDR, NIR, BLC, Dual ICR, 2.8/4mm Lens 25m IR, IP66, Metal Housing, Audio In
		TC-NC9100S3E-2MP-E-I5S	PoE, H.264 High Profile, 0.002lux 1080P@25/30fps, WDR, NIR, BLC, Dual ICR, 6mm Lens 30-50m IR with 4 Array LEDs, IP66, Audio In/Out, Alarm In, USB
		TC-NC9200S3E-2MP-E-I3S	PoE, H.264 High Profile, 0.002lux 1080P@25/30fps, WDR, NIR, BLC, Dual ICR, 2.8/4mm Lens 30m IR, IP66, Metal Housing, Audio In/Out, Alarm In, USB
	<b>Starlight 960P</b>		TC-NC9400S3E-MP-E-I
		TC-NC9500S3E-MP-E-I	<b>PoE</b> , H.264 High Profile, 0.002lux 960P@25/30fps, WDR, NIR, BLC, Dual ICR, 2.8/4mm Lens 20m IR, IP66, Metal Housing
		TC-NC9500S3E-MP-E-I2	<b>PoE</b> , H.264 High Profile, 0.002lux 960P@25/30fps, WDR, NIR, BLC, Dual ICR, 2.8/4mm Lens 25m IR, IP66, Metal Housing, Audio In
		TC-NC9400S3E-MP-E-I5	<b>PoE</b> , H.264 High Profile, 0.002lux 960P@25/30fps, WDR, NIR, BLC, Dual ICR, 6mm Lens 30-50m IR, IP66, Metal Housing
		TC-NC9500S3E-MP-E-I3	<b>PoE</b> , H.264 High Profile, 0.002lux 960P@25/30fps, WDR, NIR, BLC, Dual ICR, 2.8/4mm Lens 30m IR, IP66, Metal Housing
		TC-NC9200S3E-MP-E-I3 Full Interfaces	<b>PoE</b> , H.264 High Profile, 0.002lux 960P@25/30fps, WDR, NIR, BLC, Dual ICR, 2.8/4mm Lens 30m IR, IP66, Metal Housing, Audio In/Out, Alarm In, USB
		TC-NC9100S3E-MP-E-I5 Full Interfaces	<b>PoE</b> , H.264 High Profile, 0.002lux 960P@25/30fps, WDR, NIR, BLC, Dual ICR, 6mm Lens 30-50m IR, IP66, Audio In/Out, Alarm In, USB
		TC-NC9100S3E-MP-E-I8 Full Interfaces	<b>PoE</b> , H.264 High Profile, 0.002lux 960P@25/30fps, WDR, NIR, BLC, Dual ICR, 16mm Lens 80m IR with 4 Array LEDs, IP66, Audio In/Out, Alarm In, USB
<b>DarkFighter Starlight PTZ</b>		TC-NH9606S6-2MPIR-S-CP <b>24x Optical/16x Digital</b>	1/1.8" Sony Starlight sensor, 1080P@25/30fps IR distance 120-150meters; Speed 0.05°~400°/s, SDHC card(64GB) TVS 6000V protection; IP66 waterproof <b>Low Illumination: 0.002Lux</b>
		TC-NH9806S6-2MPIR-S <b>30x Optical/16x Digital</b>	1/1.8" Sony Starlight sensor, 1080P@25/30fps IR distance 150-180meters; Speed 0.05°~400°/s, SDHC card(64GB) TVS 6000V protection; IP66 waterproof, Wiper <b>Low Illumination: 0.002Lux</b>
		H.265 Auto-tracking TC-NH9806S6-2MPIR-S-A <b>30x Optical/16x Digital</b>	1/1.8" Sony Starlight sensor, H.265 Compression Technology, 1080P@25/30fps, Auto-tracking and Advanced IVA functions, IR distance 150-180meters; Speed 0.05°~400°/s, SDHC card(64GB) TVS 6000V protection; IP66 waterproof, Wiper <b>Low Illumination: 0.002Lux</b>

The Choice of New Generation Smart IP Solutions

SMART PTZ			
Series	Image	Model	Specifications
<b>H.265 33X 3MP</b>		TC-NH9906S6-3MPIR-CW-I 33xOptical/16x Digital	1/2.8" Sony Exmor CMOS sensor, 3MP@25/30fps IR distance 120meters; Speed 0.05°~400°/s, SDHC card(64GB) 24 Privacy Mask, TVS 6000V protection; IP66 waterproof, Wiper Smart IVA fucntions:Tripwire/Perimeter/Object Lost&Left/Running/Parking/Loitering/Crowd/On-duty Detection
		TC-NH9906S6-3MP-I 33xOptical/16x Digital	1/2.8" Sony Exmor CMOS sensor, 3MP@25/30fps Speed 0.05°~600°/s, SDHC card(64GB),24 Privacy Mask, TVS 6000V protection; IP66 waterproof,Smart IVA fucntions:Tripwire/Perimeter/Object Lost&Left/Running/Parking/Loitering/Crowd/On-duty Detection
<b>1080P Auto-tracking</b>		TC-NH9806S6-2MPIR-A 30X Optical/16x Digital	1/2.8" 3.27Megapixel Sony Exmor CMOS sensor, 1080P@25/30fps IR distance 150meters; Speed 0.05°~400°/s, SDHC card(64GB) 24 Privacy Mask, TVS 6000V protection; IP66 waterproof, Wiper <b>*Support Panorama auto-tracking; Tripwire&amp;Perimeter trigger auto-tracking; People accounting;</b>
		TC-NH9606S6-2MPIR-A 20X Optical/16x Digital	
		TC-NH9806S6-2MP-A 30X Optical/16x Digital	1/2.8" 3.27Megapixel Sony Exmor CMOS sensor, 1080P@25/30fps Speed 0.05°~600°/s, SDHC card(64GB), 24 Privacy Mask TVS 6000V protection; IP66 waterproof, Wiper <b>*Support Panorama auto-tracking; Tripwire&amp;Perimeter trigger auto-tracking; People accounting;</b>
		TC-NH9606S6-2MP-A 20X Optical/16x Digital	
<b>1080P</b>		TC-NH9806S6-2MPIR-CW 30X Optical/16x Digital	1/2.8" 2.1Megapixel Sony Exmor CMOS sensor, 1080P@25/30fps IR distance 120meters, Speed 0.05°~400°/s, Mirco SD card(32GB) TVS 6000V protection; IP66 waterproof, Wiper <b>*Support Tripwire&amp;Perimeter intelligent analysis functions</b>
		TC-NH9606S6-2MPIR-CW 20X Optical/16x Digital	
		TC-NH9806S6-2MP 30X Optical/16x Digital	1/2.8" 2.1Megapixel Sony Exmor CMOS sensor, 1080P@25/30fps Speed 0.05°~600°/s, Mirco SD card(32GB) TVS 6000V protection; IP66 waterproof <b>*Support Tripwire&amp;Perimeter intelligent analysis functions</b>
		TC-NH9606S6-2MP 20X Optical/16x Digital	
		TC-NH9616S6-2MP 20x Optical/16x Digital	1/2.8" 2.1Megapixel Sony Exmor CMOS sensor 1080P@25/30fps, speed 0.05°~600°/s, Mirco SD card(32GB) Multiple-functional IVA; Triple-stream; WDR TVS 6000V protection; Indoor in-ceiling mount
<b>960P</b>		TC-NH9406S6-MPIR-CW 20X Optical/16x Digital	1/3" 1.3Megapixel Progressive CMOS sensor, 960P@25/30fps IR distance 120meters, Speed 0.05°~400°/s, Mirco SD card(32GB) TVS 6000V protection; IP66 waterproof <b>*Support Tripwire&amp;Perimeter intelligent analysis functions</b>
		TC-NH9406S6-MP 20X Optical/16x Digital	1/3" 1.3Megapixel Progressive CMOS sensor, 960P@25/30fps Speed 0.05°~600°/s, Mirco SD card(32GB) TVS 6000V protection; IP66 waterproof <b>*Support Tripwire&amp;Perimeter intelligent analysis functions</b>
<b>Bracket</b>		TC-DF20/21	TC-DF20: Wall mount bracket for speed dome TC-DF21: Pendant mount bracket for speed dome

The Choice of New Generation Smart IP Solutions

Smart NVR			
Series	Image	Model	Specifications
<b>H.265 Standard</b>		TC-NR2005M7-S1	5ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;1ch 4K/6MP/5MP/4MP, 2ch 3MP, 4ch 1080P, 5ch 720P/4CIF Realtime Display;1ch 4K/6MP/5MP/4MP, 2ch 3MP, 4ch 1080P/720P/4CIF Sync playback;Support IVA function, 1SATA, 1 HDMI&VGA,2USB
		TC-NR2010M7-S1	10ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;1ch 4K/6MP/5MP/4MP, 2ch 3MP, 4ch 1080P, 5ch 720P/4CIF Realtime Display;1ch 4K/6MP/5MP/4MP, 2ch 3MP, 8ch 1080P/720P/4CIF Sync playback;Support IVA function, 1SATA, 1 HDMI&VGA,2USB
		TC-NR2020M7-S1	20ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;1ch 4K/6MP/5MP/4MP, 2ch 3MP, 4ch 1080P, 5ch 720P/4CIF Realtime Display;1ch 4K/6MP/5MP/4MP, 2ch 3MP, 8ch 1080P/720P/4CIF Sync playback;Support IVA function, 1SATA, 1 HDMI&VGA,2USB
		TC-NR2020M7-S2	20ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P, 20ch 720P/4CIF Realtime Display;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P/720P/4CIF Sync playback;Support IVA function, 2SATA, 1 HDMI&VGA,2USB
		TC-NR2020M7-S4	20ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P, 20ch 720P/4CIF Realtime Display;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P/720P/4CIF Sync playback;Support IVA function, 4SATA, 1 HDMI&VGA,2USB
		TC-NR2040M7-S4	40ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P, 32ch 720P, 40ch 4CIF Realtime Display;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P/720P/4CIF Sync playback;Support IVA function, 4SATA, 1 HDMI&VGA,2USB
<b>H.265 RAID</b>		TC-NR2020M7-S8	20ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P, 20ch 720P/4CIF Realtime Display;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P/720P/4CIF Sync playback;Support IVA function, 8SATA, 2 HDMI&VGA,3USB, Support Raid 0,1,5,10
		TC-NR2040M7-S8	40ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P, 32ch 720P, 40ch 4CIF Realtime Display;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P/720P/4CIF Sync playback;Support IVA function, 8SATA, 2 HDMI&VGA,3USB, Support Raid 0,1,5,10
		TC-NR2080M7-S8	80ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P, 32ch 720P, 64ch 4CIF Realtime Display;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P/720P/4CIF Sync playback;Support IVA function, 8SATA, 2 HDMI&VGA,3USB, Support Raid 0,1,5,10
<b>H.265 RAID&amp;Hot-Swap</b>		TC-NR2020M7-E8	20ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P, 20ch 720P/4CIF Realtime Display;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P/720P/4CIF Sync playback;Support IVA function, 8SATA, 2 HDMI&VGA,3USB; Support Raid 0,1,5,10
		TC-NR2040M7-E8	40ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P, 32ch 720P, 40ch 4CIF Realtime Display;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P/720P/4CIF Sync playback;Support IVA function, 8SATA, 2 HDMI&VGA,3USB; Support Raid 0,1,5,10
		TC-NR2080M7-E8	80ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P, 32ch 720P, 64ch 4CIF Realtime Display;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P/720P/4CIF Sync playback;Support IVA function, 8SATA, 2 HDMI&VGA,3USB; Support Raid 0,1,5,10
		TC-NR2080M7-E16	80ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P, 32ch 720P, 64ch 4CIF Realtime Display;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P/720P/4CIF Sync playback;Support IVA function, 16SATA, 2 HDMI&VGA,3USB; Support Raid 0,1,5,10
		TC-NR2160M7-E16	160ch 4K/6MP/5MP/4MP/3MP/1080P/720P/4CIF IP Camera Input;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P, 32ch 720P, 64ch 4CIF Realtime Display;4ch 4K/6MP, 5ch 5MP, 8ch 4MP, 9ch 3MP, 16ch 1080P/720P/4CIF Sync playback;Support IVA function, 16SATA, 2 HDMI&VGA,3USB; Support Raid 0,1,5,10

The Choice of New Generation Smart IP Solutions

Smart NVR			
Series	Image	Model	Specifications
<b>PoE NVR</b>		TC-NR1004M7-P1-T	<b>4ch</b> 1080P/720P IP Camera Input, 4ch Realtime Display/ Sync Playback; Up to 6MP Resolution Recording; Bandwidth: 40Mbps/40Mbps I/O Plug&Play with up to 4 Independent PoE Network Interfaces HDMI, VGA Output, 2 USB, Alarm Output, 1 SATA(Up to 6TB)
		TC-NR1004M7-P2-T	<b>4ch</b> 1080P/720P IP Camera Input, 4ch Realtime Display/ Sync Playback; Up to 6MP Resolution Recording; Bandwidth: 80Mbps/80Mbps I/O Plug&Play with up to 4 Independent PoE Network Interfaces HDMI, VGA Output, 2 USB, Alarm Output, 2 SATA(Up to 12TB)
		TC-NR1008M7-P2-T	<b>8ch</b> 1080P/720P IP Camera Input, 8ch Realtime Display/ Sync Playback; Up to 6MP Resolution Recording; Bandwidth: 80Mbps/80Mbps I/O Plug&Play with up to 8 Independent PoE Network Interfaces HDMI, VGA Output, 2 USB, Alarm Output, 2 SATA(Up to 12TB)
		TC-NR1016M7-P2-T	<b>16ch</b> 1080P/720P IP Camera Input, 16ch Realtime Display/ Sync Playback; Up to 6MP Resolution Recording; Bandwidth: 128Mbps/64Mbps I/O Plug&Play with up to 8 Independent PoE Network Interfaces HDMI, VGA Output, 2 USB, Alarm Output, 2 SATA(Up to 12TB)
		TC-NR1016M7-P4-T	<b>16ch</b> 1080P/720P IP Camera Input, 16ch Realtime Display/ Sync Playback; Up to 6MP Resolution Recording; Bandwidth: 128Mbps/64Mbps I/O Plug&Play with up to 8 Independent PoE Network Interfaces HDMI, VGA Output, 2 USB, Alarm 16/4 I/O, 4 SATA(Up to 24TB)
<b>NVR Standard</b>		TC-NR1004M7-S1	<b>4ch</b> 1080P/720P IP Camera Input, 4ch Realtime Display; 2ch 1080P/4ch 720P Sync Playback, 40Mbps Bandwidth HDMI, VGA Output, 1 SATA(Up to 4TB)
		TC-NR1004M7-S2	<b>4ch</b> 1080P/720P IP Camera Input, 4ch Realtime Display; 2ch 1080P/4ch 720P Sync Playback, 40Mbps Bandwidth HDMI, VGA Output, 2 SATA(Up to 8TB)
		TC-NR1008M7-S2	<b>8ch</b> 1080P/720P IP Camera Input, 8ch Realtime Display; 2ch 1080P/4ch 720P Sync Playback, 40Mbps Bandwidth HDMI, VGA Output, 2 SATA(Up to 8TB)
		TC-NR1016M7-S2	<b>16ch</b> 1080P/720P IP Camera Input, 16ch Realtime Display; 8ch 720P/4ch 1080P Sync Playback, Bandwidth: 128Mbps/64Mbps I/O HDMI, VGA Output, 2 SATA(Up to 8TB)
<b>NVR Professional</b>		TC-NR1016M7-S4	<b>16ch</b> 1080P/720P IP Camera Input, 16ch Realtime Display; 8ch 720P/4ch 1080P Sync Playback, Bandwidth: 128Mbps/64Mbps I/O HDMI, VGA Output, 4 SATA(Up to 16TB)
		TC-NR1016M7-S8	<b>16ch</b> 1080P/720P IP Camera Input, 16ch Realtime Display; 16ch 720P/8ch 1080P Sync Playback, Bandwidth: 200Mbps/120Mbps I/O HDMiX2, VGA Output, Alarm I/O: 16/4 RJ45x2(1000M), 8 SATA(Up to 32TB)
		TC-NR1032M7-S8	<b>32ch</b> 1080P/720P IP Camera Input, 32ch Realtime Display; 16ch 720P/8ch 1080P Sync Playback, Bandwidth: 200Mbps/120Mbps I/O HDMiX2, VGA Output, Alarm I/O: 16/4 RJ45x2(1000M), 8 SATA(Up to 32TB)

1/ Based on Exworks Terms Tianjin in US Dollars  
3/ Warranty: 2 Years after Shipping Date

2/ Terms of Payment: T/T in Advance  
4/ Price Validity: 30 Days

The Choice of New Generation Smart IP Solutions